Quote Request Form

Phone: (724) 925-2164 Fax: **(724) 925-3202**



J&M Fluidics, Inc. • 851 Tech Drive • Telford, PA 18969

Chiller Information	
Company Name:	Date:
Email:	Contact:
Telephone Number:	Fax Number:
Condensing Method: Air-Cooled or Water-Cooled Packaged or Split System (A	sir-Cooled Only)
Ambient Air Temp:°F (For Air-Cooled Units) or Entering Condenser Water Temp:°F (For Water-Cooled Units)	
Fluid To Be Cooled: Water Propylene Glycol	%
Ethylene Glycol% Other	
Entering Fluid Temperature°F Leaving Fluid Temperature°F (Please Specify in Detail)	
Fluid Flow Rate:GPM orLB / HR	
Power Requirement: Voltage Phase	Cycle
Required Capacity (BTUH): Fluid Storage Tank Model Required: Yes No	
Ausilable Ordiana	
Available Options	
Remote Idec Touchscreen Control Panel	E-Coat Condenser Coil (Coastal Protection)
Industrial VPN Router	Polyester Coated Condenser Coil (Coastal Protection)
5 Port Ethernet Switch	Copper Fin Condenser Coil (Coastal Protection)
4 Year Extended Warranty On Compressor Only	Semi-Hermetic Compressor
Variable Fan Speed Control	Compressor Cylinder Unloading - Semi-Hermetic Only
ECM (Digital) Fan Motor	Hot Gas Bypass Capacity Control
Receiver / Head Pressure Control (0°F)	(Semi-Hermetic Only, Standard on Scroll Units)
Heated Receiver / Head Pressure Control (-20°F)	Special Evaporator and Piping for De-Ionized Water
Fused Process Pump (Stainless Steel)	Tank Sight Glass
Dual Fused Process Pumps w/ Manual Switchover (Stainless Steel)	Tank Low Level Indicator
Dual Fused Process Pumps w/ Auto Switchover (Stainless Steel)	Process Water Pressure Gauge Set
Process Pump VFD (Variable Frequency Drive)	Low Flow Bypass
Compressor Fusing	Condenser Water Regulating Valve
Compressor VFD (Variable Frequency Drive) - most models	(Water Cooled Models Only)
Phase Monitor	Non-Fused Disconnect
115 Service Outlet (raintight)	Fused Disconnect
Casters - Factory Mounted	
Factory Installed Heat Tape Freeze Protection (For ambient temperatures only)	